

## Talbert Architectural Panel & Door, Inc 711 S Stimson Avenue City of Industry, CA 91745

Tel: 714.671.9700 Fax: 714.671-9770

## Instructions for Maintenance & Care UV-Cured Architectural Millwork Finish

Architectural panels, doors, and components finished with Talbert's Perfecta UV finishing system require little maintenance to preserve their appearance, but certain simple steps should be taken to maintain the beauty for years to come.

Our UV-cured finish is highly resistant to a vast number of substances, but the most common contaminant will be dust. Dust can act as a micro-abrasive, so care should be exercised in its removal. To remove it, use a soft lint-free cloth moistened with water; no special chemicals are needed. After cleaning, buff the surface as needed with a soft, dry cloth to remove any remaining smudges or fingerprints. It is NOT recommended to use commercially available citrus cleaners, detergents, oils, impregnated cleaning pads, waxes, or polishes.

In the event of a liquid spill, use an absorbent cloth or sponge to remove the liquid WITHOUT wiping. Once the liquid is virtually gone, use a water-saturated soft cloth to wipe the surface clean. Buff with a soft dry cloth to remove any streaks. Incidental contact with liquids (even red wine) will not harm the finish if properly removed.

Care should be taken to shield all fine wood products from the damaging effects of the sun. Prolonged exposure can irreversibly alter the color of the wood and affect both the value and the enjoyment of your investment.