



711 Stimson Ave, City of Industry, CA 91745
 PH (714)671-9700 FAX 714)671-9770

MACHINING FORM

CUSTOMER: _____ PAGE: _____ OF _____
 JOB: _____ DATE: _____
 DRAWN BY: _____

Note: Any and all changes must be submitted to Talbert Architectural in writing. No verbal changes will be accepted. Accuracy of information is the responsibility of the customer.

HINGE MFG: _____
HANDING: _____

HINGE #: _____
 SIZE _____
 BACKSET _____
 THICKNESS _____
 PIVOT _____
 TEMPLATE NO. _____

HINGE CORNERS
 1/4" Radius
 5/8" Radius
 Square
 None

3 degree BEVELS
 Lock Edge
 Hinge Edge
 None

NOTE:
 WHEN WIRE CHASE IS REQUIRED, DESIGNATE
 HINGE TO RECEIVE WIRE WITH AN "X"

FACE SPECIES, CUT & GRADE:

NET DOOR SIZE:

DOOR RATING

ACTIVE

LOCKS / EXIT DEVICES

	BORED LOCK	DEAD LOCK
FACE BORE	_____	_____
BOLT BORE	_____	_____
BACKSET	_____	_____
F-P THICKNESS	_____	_____
F-PLATE WIDTH	_____	_____
F-P HEIGHT	_____	_____

FACE PLATE CORNERS
 1/4" Radius
 5/8" Radius
 Square
 NONE

DEVICE TYPE

BORED LOCK (161)	EXIT DEVICE (RIM / SVR)
DEAD LOCK (86 & 161)	EXIT DEVICE (MORTISE)
MORTISE LOCK (86)	EXIT DEVICE (CVR / CVC)
	NONE

MANUFACTURER _____
 TEMPLATE NO. _____
 FUNCTION NO. _____
ADDITIONAL PREP:

NOTE: * EXIT DEVICE BACK-SET SHALL BE GIVEN AS THE DISTANCE FROM C-L OF DEVICE TO C-L OF DOOR THICKNESS AT LOCK STILE UNLESS OTHERWISE NOTED.

INACTIVE

STRIKES

1-1/4 X 4-7/8" ASA
 1-1/8 X 2-3/4" LIP
 1-1/8 X 2-3/4" D-BOLT

DUSTBOX
 OTHER _____
 MFG. _____
 TEMP. _____

FLUSH BOLTS
 MFG. _____
 TEMP. NO. _____
 CORNER PRE _____

3 degree BEVELS
 Lock Edge
 Hinge Edge
 None

RABBET A
RABBET B
HINGE STILE
LOCK STILE
TOP RAIL

DOOR NUMBERS, HANDING & ANY OTHER NOTES FOR THIS PAGE

SPEC. NO.

ITEM or ID#

Approval: _____